No.	Question
1	Why must the controls be isolated before each load can be attached or disconnected by the slinger?
2	Describe a physical method of checking that a bucket is fully secured to the quick-hitch coupler prior to work.
3	What THREE main duties of the Health and Safety at Work Act must employees follow?
4	When working in a confined area or space: a) what danger can be present with regards to the counterweight of the machine, b) when should measures be taken and c) what measures should be implemented?
5	What is the purpose of a risk assessment?
6	When must a banksman/signaller be used before moving an excavator?
7	What are the possible outcomes of prosecution for not complying with legislation and regulations?
8	If both travel levers (or travel pedal for wheeled machines) are pushed forwards when the track motors (or driving wheels) are in front of the cab, in which direction would the machine move?
9	Why are plant operators generally regarded as 'safety-critical' workers?
10	According to legislation, when are check valves and a rated capacity or load moment indicator required?
11	The operator has been asked to drive the machine onto a transporter/trailer. a) Who is responsible for the loading operations and b) state FOUR actions to be considered by the operator before loading commences?
12	Explain ALL visual checks that must be carried out on all types of quick-hitch bucket attaching systems before use.

I	Why must the cost halt he ware aver with the coh door closed?
	Why must the seat belt be worn, even with the cab door closed?
13	
	Give THREE reasons why an oversize bucket should NOT be used when excavating trenches to
14	specification.
	Cable avoidance tools (CATs) can detect a variety of buried services. What type of material do
15	they have limitations in locating?
	On a semi-automatic quick-hitch bucket attaching system:
	a) what is the purpose of the safety pin and b) what checks MUST be made to the pin before use?
16	by what checks wost be made to the pill before use:
17	If setting up to work in a pedestrianised area, state THREE factors that need to be taken into account.
	Name TWO types of equipment used to ensure that excavation levels, measurements and
18	positions are to the required specification.
10	
	Give TWO examples of where The Work at Height Regulations may apply to 360 excavator
19	operations.
	Apart from the operator, who else may need to use the machine's Operator's Manual?
20	
	Using the Operator's Manual, state the cold-starting procedure for the machine.
	Note: The Operator's Manual for the machine being used for the test MUST be available for
21	reference by the candidate.
22	When slewing with a load, where should the operator be looking?
	Why must excavator operators not begin to load vehicles until the forward-tipping dumper
23	driver is clear of their machine?
25	
	What information does the 'dig-envelope' (also known as 'working range') chart give?
24	(Candidates may be shown a copy of a chart.)
	With regards to lifting accessories, irrespective of who supplied the accessories, what THREE
25	factors should be ensured before the accessories are used?
	If the machine is being travelled or working on the public highway, the Road Traffic Act
	applies.
26	 a) What type of licence and which class should the operator hold and b) what is the minimum age allowed?
	.,
	If setting up to excavate in a confined area, name TWO things that should be taken into
27	account before starting.

28	The safe working load (SWL) or working load limit (WLL) of a multi-leg chain sling only applies in what TWO conditions or configurations?
29	When parking the machine at the end of the shift, name THREE places where the machine should NOT be parked.
30	Why is it important that the bucket/attachment is lowered and the engine switched off before the operator exits the cab?
31	Give FOUR reasons that may cause the machine to tip over – forwards and/or sideways.
32	If attaching accessories to a quick-hitch coupler, give TWO reasons why the coupler should be tilted in the downwards position (ram extended)?
33	a) What is the purpose of a Method Statement and b) what is required of the operator?
34	What is the nearest distance allowed to gas pipes when excavating with the machine?
35	Why should an excavator be re-fuelled at the end of the day?
36	In what situation does a hard hat NOT need to be worn when operating a 360 excavator?
37	If the excavator is carrying out deep excavating work using the full working range, what hazard may occur?
38	If a yellow-coloured marker tape is unearthed during excavating, which TWO types of services could this indicate?
39	If the operator has loaded the machine onto a transporter/trailer on behalf of a driver, what checks must be carried out before they leave the cab?
40	What is the purpose of the counterweight of the machine?
41	 a) What determines the minimum distances that any part of plant and machinery has to be kept from over head electricity lines and b) explain why a distance should be kept.
42	Which parts of the machine is the radius (for lifting) measured from?
43	What is the purpose of a roll or ROPS frame?

4.4	Explain the purpose of a lift plan.
44	
45	State the purpose of the check valve(s) located on the boom cylinder rams.
46	Who determines the lifting/object handling capacity of the machine?
47	What does the Health and Safety at Work etc. Act require employers to do, specifically regarding plant?
48	What is the definition of, or how can a hazard be described?
49	If a hook is fitted to the machine for lifting purposes, what must be checked before use?
50	If the operator has to top-up the hydraulic oil, state TWO precautions to ensure cleanliness of the system.
51	Manufacturers' lifting or object handling capacity charts apply (in all known cases) when the machine is level. What is the effect if a load is lifted or travelled facing downhill on a downhill slope?
52	Accessories must only be attached to manufacturers' approved lifting points. Explain THREE possible consequences if the recommendations are not followed.
53	Before leaving the cab for a rest break, after parking and switching off the machine, what final action must be carried out?
54	Using the lifting capacity diagram for A59: a) if the machine is equipped with a 2.5 m long dipper, what is the maximum lifting capacity in tonnes at a 6 m radius/reach over the sides of the track with the load at 3 m height b) in principle, if a longer dipper is fitted, what effect does that have on the lifting capacity (assuming same size bucket and machine configuration)?
55	Name THREE ways that a plant operator can contribute towards repeat business with the client or principal contractor.
56	What makes up the total (or gross) weight of a load that is to be lifted?
57	Why should different soils be segregated during excavating?
58	a) Why should the slewing direction be to the left wherever possible and b) Explain why.
59	If checking the oil level using a dipstick, why must gloves be worn?
60	What effect can a swinging load have on an excavator?

61	What is the main purpose of the Rated Capacity Indicator (RCI) or Load Moment Indicator (LMI)?
62	If the machine's rated capacity/object handling capacity chart is not available for reference, what other method can be used to determine the machine's lifting capacity?
63	What factors determine the shoring requirements of a trench?
64	Name THREE ways in which an operator can minimise their impact upon the environment whilst using the machine.
65	If the accessory attachment point is not part of the bucket, give TWO reasons why it should be removed.
66	The operator has to fit and use a new bucket using a quick-hitch coupler that they are unfamiliar with. What do Regulations (i.e. PUWER 98) and other guidance require the operator to have?
67	Before lowering into or moving a drag box into a trench, what trench-related checks must be made?
68	If travelling with a load, name FIVE factors that must be taken into account by the operator before moving.
69	When an object needs to be lifted on a site, what should be the first consideration of planning?
70	If a trench has a depth of 2 metres: a) What is the minimum distance to maintain from the edge of the trench when placing spoil and b) explain why?
71	How can a qualification or card benefit a plant operator?
72	Describe TWO actions to be taken for an open trench at the end of a working day.
73	What is the meaning of this hand signal (being demonstrated by the tester)?
74	Why should long loads be lifted using a swivelling type lifting accessory?
75	Name FOUR different types or levels of disciplinary actions or sanctions that can be applied (by employers and judicial bodies) to operators of plant who do not comply with or follow legislation and regulations.

76	Using the operator's manual, state the figure for setting track tension. For wheeled units, state the tyres' operating pressure. Note: The operator's manual for the machine being used for the test MUST be available for reference by the candidate.
77	Give TWO reasons why, wherever possible, operators should excavate the ground in layers.
78	What is regarded as the danger or hazard zone during a lifting operation?
79	What particular and specific hazards can affect the stability of the machine when working on old industrial (brownfield) sites?
80	If the load inadvertently or accidentally lands, what course of action should be taken?
81	What needs to be inspected on a quick-hitch coupler when attaching lifting accessories to lift slung loads?
82	During work, the engine starts to overheat. Explain the danger if someone tries to remove the radiator or expansion tank cap.
83	List SIX typical subject areas that should be covered in a site induction.
84	On both tracked and wheeled types: a) what differs between lifting over the side compared to over the front or the rear of the machine? b) Explain why.
85	Before manually changing any bucket: a) Where should the bucket be positioned (in relation to the ground) before removing the final pin and b) explain why?
86	Where should the excavator's operator's manual be kept and why?
87	The operator is asked to excavate a new trench. State FIVE different requirements that must be considered or implemented before work commences.